

NUMBER : TSNH00374097-S1

Applicant : TAMCO SUMMIT VEHICLE JIANGMEN CO.,LTD. ROOM 910 BUILDING 2,KINWAI PLAZA,No,213,BAISHI AVENUE, PENGJIANG DISTRICT JIANGMEN CITY GUANGDONG CHINA Attn :COCO TAN

Photo



To be continued

Authorized By : For Intertek Testing Services (Tianjin) Ltd.

David Zhang Asst.General Manager





intertek

Test Report

	NUMBER	: TSNH00374097-S1			
Sample Description: One (1) submitted sample said t Item Name Item No. Style No. Age grading Supplier Country of Origin	(1) submitted sample said to be Name : RIDE ON MOTORCYCLE No. : TAMCO 1200,1200,1300 e No. : TAMCO 1200,1200,1300 grading : 3-8Y plier : TAMCO SUMMIT VEHICLE JIANGMEN CO.,LTD.				
	or details refer to attached page(s).	****			
Conclusion:					
<u>Tested Sample/Components</u> Submitted Sample	<u>Standard</u> U.S. ASTM F963-17 Standard Consumer Safety Specification for Toy Safety – Physical and mechanical test and Flammability part	<u>Result</u> Pass			
(16)	U.S. ASTM F963-17 for total Lead content-surface coating	Pass			
(1,2&3),(4,5&6),(7,8&9), (10,11&32),(12,13&14), (15),(17),(18),(19),(20),(21), (22),(23),(24),(25),(26),(27), (28),(29,30&31),(33)&(34)	U.S. ASTM F963-17 for total Lead content-non- surface coating	Pass			
(1),(2),(3),(4),(5),(6),(7),(8), (9),(10),(11),(12),(13),(14), (15),(17),(18),(19),(20), (21),(22),(23),(24),(25),(26), (27),(28),(29),(30),(31),(32), (33)&(34)	U.S. ASTM F963-17 section 4.3.5.2(2)(b) for soluble elements content for non-surface coating materials	Pass			
(16)	U.S. ASTM F963-17 for soluble elements content in surface coating	Pass			
***********	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	To be continued			

To be continued

Authorized By : For Intertek Testing Services (Tianjin) Ltd.

David Zhang Asst.General Manager





intertek

Test Report

NUMBER : TSNH00374097-S1

(16)	U.S. Code of Federal Regulations title 16 part 1303 for total Lead content in surface coating	Pass
(16)	U.S. Consumer Product Safety Improvement Act 2008 title I, section 101 for total Lead content in surface coating	Pass
(1,2&3),(4,5&6),(7,8&9), (10,11&32),(12,13&14), (15),(17),(18),(19),(20),(21), (22),(23),(24),(25),(26),(27), (28),(29,30&31),(33)&(34)	U.S. Consumer Product Safety Improvement Act 2008 title I, section 101 for total Lead content in non-surface coating materials (substrate)	Pass
(1,2&3),(4,5&6),(7,8&9), (10,11&32),(12,13&14), (15),(16),(17),(18),(19),(20), (21),(22),(23),(24),(25),(26), (27),(28)&(33)	US Consumer Product Safety Improvement Act 2008 Title I, Sec 108(a) & (b)(3) and US 16 CFR Part 1307 for Prohibition of Children's Toys and Child Care Articles Containing Specified Phthalates	Pass
Submitted Sample	Consumer Product Safety Improvement Act (CPSIA) 2008 Section 103 Tracking Labels for Children Products	Pass
(35),(36),(37)	U.S. ASTM F963-23 for total Lead content in non- surface coating materials	Pass
(35),(36),(37)	U.S. ASTM F963-23 for soluble elements content	Pass
(35),(36),(37)	U.S. Consumer Product Safety Improvement Act 2008 title I, section 101 and its amendment for total Lead content in non-surface coating materials (substrate)	Pass
(35),(36),(37)	15 U.S.C. Sec. 1278a - Total Lead Content	Pass
(35),(36),(37)	US Consumer Product Safety Improvement Act 2008 Title I, Sec 108(a) & (b)(3) and US 16 CFR Part 1307 for Prohibition of Children's Toys and Child Care Articles Containing Specified Phthalates	Pass
************	*****	*********************************

To be continued

Authorized By : For Intertek Testing Services (Tianjin) Ltd.

David Zhang Asst.General Manager







NUMBER : TSNH00374097-S1

1. Toy Tests

As per ASTM Standard Consumer Safety Specification for Toy Safety F963-17.

Applicant's Specified Age Group for Testing: For ages from 3 to 8 years

The submitted samples were undergone the use and abuse tests in accordance with the Federal Hazardous					
Substances Act (FHSA), Title 16, Code of Federal Regulations: -					
Test	FHSA	Parameter			
Tip over Test	Section 1500.53(b)	3 times			
Torque Test	Section 1500.53(e)	4 in-lbf			
Tension Test	Section 1500.53(f)	15 lbf			
Compression Test	Section 1500.53(g)	30 lbf			

<u>Section</u>	Testing Items	<u>Assessment</u>
4.1	Material Quality	Р
4.2	Flammability	P (See test data #1)
4.3.7	Stuffing Materials	NA
4.4	Electrical/Thermal Energy	NA
4.5	Sound-Producing Toys	Р
4.6.1	Toys Intended for Children under 36 Months (Small Objects)	NA
4.6.2	Mouth-Actuated Toys	NA
4.6.3	Toys And Games for 36 Months to 72 Months (Small Part Warning)	Р
4.7	Accessible Edges	Р
4.8	Projections	Р
4.9	Accessible Points	Р
4.10	Wires Or Rods	NA
4.11	Nails And Fasteners	Р
4.12	Plastic Film	Р
4.13	Folding Mechanisms and Hinges	NA
4.14	Cords, Straps, and Elastics	NA
4.15	Stability and Over-Load Requirements	Р
4.16	Confined Spaces	NA
4.17	Wheels, Tires and Axles	Р
4.18	Holes, Clearance, and Accessibility of Mechanisms	Р
4.19	Simulated Protective Devices	NA
4.20	Pacifiers	NA
4.21	Projectile Toys	NA
4.22	Teethers and Teething Toys	NA
4.23	Rattles	NA
4.24	Squeeze Toys	NA
4.25	Battery-Operated Toys	P (See test data #2)

Page 4 of 20



<u>Test Report</u>

ntertek

Total Quality. Assured.

ſ

Section	Testing Items	Assessment
4.26	Toys Intended to be Attached to a Crib or Playpen	NA
4.27	Stuffed and Beanbag-Type Toys	NA
4.28	Stroller and Carriage Toys	NA
4.29	Art Materials	NA
4.30	Toy Gun Marking	NA
4.31	Balloons	NA
4.32	Certain Toys with Nearly Spherical Ends	NA
4.33	Marbles	NA
4.34	Balls	NA
4.35	Pompoms	NA
4.36	Hemispheric-Shaped Objects	NA
4.37	Yo Yo Elastic Tether Toys	NA
4.38	Magnets	NA
4.39	Jaw Entrapment in Handles and Steering Wheels	NA
4.40	Expanding Materials	NA
4.41	Toy Chests	NA
5	Labelling Requirement	P #1
6	Instructional Literature	P #1
7	Producer's Markings	P #1
	- Name of Producer (Toy)	Yes
	- Address (Toy)	Yes

Remark: The submitted samples were undergone the tests in accordance with Section 8.5 through Section 8.18 and 8.21 through 8.26 on normal use, abuse and specific tests for different types of toys whichever is applicable.

P = Pass NA = Not Applicable

#1 = Only artwork of instruction and packaging were provided by applicant.





NUMBER : TSNH00374097-S1

Test data #1

Flammability Test- Solid & Plush toys

As per section 4.2 of the ASTM Standard Consumer Safety Specification On Toy Safety F963-17.

Result = Did Not Ignite

Test data #2

Battery Powered Ride-On Toys

As per ASTM F963-17 consumer safety specification for toy safety section 4.25, 5.15, 6.5, 6.6 and 7.2.

Applicant's Specified Age Group for Testing: For ages from 3 to 8 years.

Type of battery: 12 V 4.5Ah, Lead-acid rechargeable battery x 1pc in vehicle (Non- Replaceable)

Charger type: Input 100-240 V A.C., Output 12 V D.C. (Provided)

Model: LKC-120050-E

Electric operated function: Battery powered motion, sound and LED light.

	Section	Testing items	<u>Assessment</u>
	4.25.1	Battery marking	Р
	4.25.2	Maximum allowable direct current potential	Р
	4.25.3	Protection against charging non-rechargeable battery	Р
	4.25.4	Accessible batteries	NA
	4.25.5	Accessible batteries that can fit completely within small part cylinder	NA
	4.25.6	Isolation of batteries of different types or capacities	Р
	4.25.7	Temperature of battery surface	Р
	4.25.8	Temperature of battery surface or combustion hazard after normal use and abuse test	Р
	4.25.9	Packaging and Instruction requirement	NA
		- 6.5 Instruction on safe usage of battery	
	4.25.10	Battery-powered ride-on toys	NR
	4.25.11	Toys that contain secondary cells or secondary batteries	NA
******		P = Pass NA = Not Applicable NR = Not Request	*****

To be continued

Page 6 of 20

Intertek Total Quality. Assured.

<u>Test Report</u>

NUMBER : TSNH00374097-S1

2. Battery Powered Ride-On Toys

As per ASTM F963-17 consumer safety specification for toy safety section 4.25, 5.15, 6.5, 6.6 and 7.2.

Applicant's specified age group for testing: For ages from 3 to 8 years

Type of battery: 12V, 4.5 Ah, Lead-acid rechargeable battery x 1pc in vehicle

Charger type: Input 100-240 V A.C., Output 12 V D.C.(Provided) Model: LKC-120050 E

Electric operated function: Battery powered motion, sound and LED light.

<u>Section</u>	Testing items	<u>Assessment</u>
4.25.1	Battery marking	Р
4.25.2	Maximum allowable direct current potential	Р
4.25.3	Protection against charging non-rechargeable battery	NA
4.25.4	Accessible batteries	NA
4.25.5	Accessible batteries that can fit completely within small part cylinder	NA
4.25.6	Isolation of batteries of different types or capacities	NA
4.25.7	Temperature of battery surface	Р
4.25.8	Temperature of battery surface or combustion hazard after normal use and abuse test	Р
4.25.9	Packaging and Instruction requirement	Р
	- 5.15 Non-replaceable battery statement in battery operated toys	Р
	- 5.15.2 Button or coin cell batteries	NA
	- 6.5 Instruction on safe usage of battery	NA
4.25.10	Battery-powered ride-on toys	Р
4.25.10.1	The maximum temperature measured on the insulation of any conductor shall not exceed the temperature rating of the material.	Р
4.25.10.2	Battery powered ride on toys shall not present a risk of fire in stalled motor test.	Р
4.25.10.3	A battery powered ride on toy designed with a wiring system that has a user replaceable device (fuse type) for the primary circuit protection or a wiring system with user resetable primary circuit protection (manual reset fuse) shall not actuate (open or trip) when tested in accordance with the nuisance tripping test	NA
4.25.10.4	Switches used in battery powered ride on toys. - Polymeric materials in switches used in battery powered ride on toys that are used to support current carrying parts shall carry a minimum flame rating of UI-94 V-0 or have a glow wire ignition rating of 750°C.	Ρ
	 The switch body shall not result in a short circuit condition when subjected to the switch endurance test and overload tests. 	
	 The switch shall not fail in a mode that could cause the vehicle to run continuously (switch stuck in the "on" position) when subjected to the 	

Page 7 of 20

intertek

Test Report

	NUMBER : TSNH0	0374097-S1
	endurance test and the overload test.	
4.25.10.5	User replaceable circuit protection devices in battery powered ride on toys.	NA
	- User replaceable circuit protection devices provided by the manufacturer in battery-powered ride-on toys shall be listed, recognized or certified by a Nationally Recognized Test Laboratory (NRTL) (that is, a laboratory recognized in accordance with 29 CFR 1910) to an appropriate electrical safety standard.	
	 All circuit protection devices used in battery powered ride on toys intended to be replaced by the user shall be replaceable only with the use of a tool or by a design which does not easily allow tempering such as a design requiring excessive force to open. 	
4.25.10.6	 Batteries and battery chargers. Battery connectors must be constructed of material with a UL94 V-0 flame rating or have a glow wire ignition rating of 750°C. The battery charging system shall not present a risk of fire due to a short circuit condition applied to any point in the length of a charger/battery. 	Ρ
	 During charging, battery-charging voltages shall not exceed the recommended charging voltages. Battery charges must be certified to the appropriate standard body. Reference document of certified body: 3175096 	
4.25.10.7	Wiring connected to the main/motor battery shall be short circuit protected and shall not present the risk of fire.	Р
4.25.10.8	Strain relief shall be provided to prevent mechanical stress on wires entering a connector block during routine maintenance.	Р
4.25.10.9	Battery powered ride on toys shall comply with the requirements for safety labelling, for additional instructional literature, and for required producer's markings. - 5.15.1 Safety warnings of battery powered ride on toys - 6.6 Instructions - 7.2 Producer's marking	Р
4.25.11	Toys that contain secondary cells or secondary batteries	NA
Remark: P =	Pass NA = Not Applicable	
#1	= The 1:1 artwork of package was provided for testing.	*****
		To be continued





NUMBER : TSNH00374097-S1

3. Total Lead (Pb) Content

As per section 4.3.5 of the ASTM standard consumer safety specification on toy safety F963-17, test method CPSC-CH-E1001-08.3, CPSC-CH-E1002-08.3 and CPSC-CH-E1003-09.1 were used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry and AAS.

(I) Surface coating

(II

<u>Tested component</u> (16)	<u>Result in ppm</u> <20	<u>Limit (ppm)</u> 90
() Non-surface coating		
Tested component (1,2&3) (4,5&6) (7,8&9) (10,11&32) (12,13&14) (15) (17) (18) (19) (20) (21) (22) (23) (24) (25) (26) (27) (28)	Result in ppm <10	Limit (ppm) 100 100 100 100 100 100 100 10
(29,30&31) (33) (34)	<10 <10 <20	100 100 100

Remark: ppm = parts per million based on dry weight of sample = mg/kg

Tested Components: See component list in the last section of this report.





NUMBER : TSNH00374097-S1

4. Soluble Elements Analysis In Non-Surface Coating Materials (Substrate Except Modelling Clay)

As per section 4.3.5.2(2)(b) of the ASTM standard consumer safety specification on toy safety F963-17, acid extraction method was used and heavy metal elements migration content were determined by Inductively Coupled Argon Plasma Spectrometry.

					Res	ult (ppn	<u>(1</u>				Limit
			2) (3			(6)	(7)	(8)	(9)	(10)	<u>(ppm)</u>
Sol. Barium (B		-	<5 <5		<5	<5	<5	<5	<5	<5	1000
Sol. Lead (Pb)			<5 <5			<5	<5	<5	<5	<5	90
Sol. Cadmium			<5 <5			<5	<5	<5	<5	<5	75
Sol. Antimony		-	<5 <5			<5	<5	<5	<5	<5	60
Sol. Selenium			<5 <5			<5	<5	<5	<5	<5	500
Sol. Chromiun		-	<5 <5		-	<5	<5	<5	<5	<5	60
Sol. Mercury (<5 <5			<5	<5	<5	<5	<5	60
Sol. Arsenic (A	As)	<2.5 <	2.5 <2.	.5 <2.5	5 <2.5	<2.5	5 <2.5	5 <2.5	<2.5	<2.5	25
					<u>Result (</u>	<u>(ppm)</u>					<u>Limit</u>
											<u>(ppm)</u>
	(11)	(12)	(13)	(14)	(15)	(17)	(18)	(19)	(20)	
Sol. Barium (Ba)	<5	<5	<5	<5	<5		<5	<5	<5	<5	1000
Sol. Lead (Pb)	<5	<5	<5	<5	<5		<5	<5	<5	<5	90
Sol. Cadmium (Cd)	<5	<5	<5	<5	<5		<5	<5	<5	<5	75
Sol. Antimony (Sb)	<5	<5	<5	<5	<5		<5	<5	<5	<5	60
Sol. Selenium (Se)	<5	<5	<5	<5	<5		<5	<5	<5	<5	500
Sol. Chromium (Cr)	<5	<5	<5	<5	<5		<5	<5	<5	<5	60
Sol. Mercury (Hg)	<5	<5	<5	<5	<5		<5	<5	<5	<5	60
Sol. Arsenic (As)	<2.5	<2.5	<2.5	<2.5	<2.5	<	:2.5	<2.5	<2.5	<2.5	25
					Result ((ppm)					<u>Limit</u>
											<u>(ppm)</u>
	(21)	(22)	(23)	(24)	(25)	(26)	(27)	(28)	(29)	(30)	
Sol. Barium (Ba)	<5	<5	6	<5	<5	<5	<5	<5	<5	<5	1000
Sol. Lead (Pb)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	90
Sol. Cadmium (Cd)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	75
Sol. Antimony (Sb)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Selenium (Se)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	500
Sol. Chromium (Cr)	<5	<5	<5	<5	<5	<5	<5	<5	<5	6	60
Sol. Mercury (Hg)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Arsenic (As)	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	25
*******	******	*******	*****	*******	*******	*******	*******	********	*******		



intertek

Total Quality. Assured.

<u>Test Report</u>

NUMBER : TSNH00374097-S1

		Limit (ppm)			
	(31)	(32)	(33)	(34)	
Sol. Barium (Ba)	<5	<5	<5	<5	1000
Sol. Lead (Pb)	<5	<5	<5	<5	90
Sol. Cadmium (Cd)	<5	<5	<5	<5	75
Sol. Antimony (Sb)	<5	<5	<5	<5	60
Sol. Selenium (Se)	<5	<5	<5	<5	500
Sol. Chromium (Cr)	<5	<5	<5	<5	60
Sol. Mercury (Hg)	<5	<5	<5	<5	60
Sol. Arsenic (As)	<2.5	<2.5	<2.5	<2.5	25

Remark: Sol. = soluble

ppm = parts per million = mg/kg

Tested components: See component list in the last section of this report.

The sample weight in bracket was for soluble heavy elements analysis only.





NUMBER : TSNH00374097-S1

5. Soluble Elements Analysis In Surface Coating

As per section 4.3.5.1(2) of the ASTM standard consumer safety specification on toy safety F963-17, acid extraction method was used and heavy metal elements migration content were determined by Inductively Coupled Argon Plasma Spectrometry.

	<u>Result (ppm)</u>	<u>Limit (ppm)</u>
	(16)	
Sol. Barium (Ba)	<5	1000
Sol. Lead (Pb)	<5	90
Sol. Cadmium (Cd)	<5	75
Sol. Antimony (Sb)	<5	60
Sol. Selenium (Se)	<5	500
Sol. Chromium (Cr)	<5	60
Sol. Mercury (Hg)	<5	60
Sol. Arsenic (As)	<2.5	25

Remark : Sol. = soluble

ppm = parts per million based on dry weight of sample = mg/kg <=less than

Tested components : See component list in the last section of this report.

6. Total Lead (Pb) Content In Surface Coating

As per standard operating procedure for determining Lead (Pb) in paint and other similar surface coatings (April 26, 2009), test method CPSC-CH-E1003-09 was used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry.

Tested Component	<u>Result (ppm)</u>	<u>Limit (ppm)</u>
(16)	<20	90
Remark: ppm = Parts per million bas < = Less Than	sed on dry weight of sample = mg	/kg
Tested Components: See componen	•	ort.
		To be continued





NUMBER : TSNH00374097-S1

7. Total Lead (Pb) Content In Non-Surface Coating Materials (Substrate)

As per standard operating procedures for determining total Lead (Pb) in children's products, test method(s) CPSC-CH-E1002-08.1 and CPSC-CH-E1001-08.1 were used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry and AAS.

Tested Components	<u>Result (ppm)</u>	<u>Limit (ppm)</u>
(1,2&3)	<10	100
(4,5&6)	<10	100
(7,8&9)	<10	100
(10,11&32)	<10	100
(12,13&14)	<10	100
(15)	<10	100
(17)	<10	100
(18)	<10	100
(19)	<10	100
(20)	<10	100
(21)	<10	100
(22)	<10	100
(23)	<10	100
(24)	<10	100
(25)	<10	100
(26)	<10	100
(27)	<10	100
(28)	<10	100
(29,30&31)	<10	100
(33)	<10	100
(34)	<20	100

Remark: ppm = Parts per million = mg/kg < = Less Than

Tested Components: See component list in the last section of this report.



intertek

Test Report

8. <u>Phthalate Content</u>

With reference to CPSC-CH-C1001-09.4, by Gas Chromatographic-Mass Spectrometric (GC-MS) analysis.

<u>Test item</u>	Result (%)					<u>Limit (%)</u> (Max.)		
	(1,28	(3)	(4,5&6)) (7,8&9)	(10	,11&32)	<u>(IMAX.)</u>
Dibutyl phthalate (DBP)	ND		ND		ND		ND	0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND)	ND		ND		ND	0.1
Benzyl butyl phthalate (BBP)	ND)	ND		ND		ND	0.1
Diisononyl phthalate (DINP)	ND)	ND		ND		ND	0.1
Diisobutyl phthalate (DIBP)	ND)	ND		ND		ND	0.1
Di-n-pentyl phthalate (DPENP)	ND)	ND		ND		ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND)	ND		ND		ND	0.1
Dicyclohexyl phthalate (DCHP)	ND)	ND		ND		ND	0.1
<u>Test item</u>			F	Result (%	<u>)</u>			Limit (%)
								<u>(Max.)</u>
	(12,13		(15)	(16)		7)	(18)	
Dibutyl phthalate (DBP)	ND		ND	ND		ID	ND	0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND		ND	ND		ID	0.01	0.1
Benzyl butyl phthalate (BBP)	ND		ND	ND		ID	ND	0.1
Diisononyl phthalate (DINP)	ND		ND	ND		ID	ND	0.1
Diisobutyl phthalate (DIBP)	ND		ND	ND		ID	ND	0.1
Di-n-pentyl phthalate (DPENP)	ND		ND	ND		ID	ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND		ND	ND		ID	ND	0.1
Dicyclohexyl phthalate (DCHP)	ND)	ND	ND	N	ID	ND	0.1
<u>Test item</u>			<u>F</u>	Result (%)			Limit (%)
	(()	(- ()	()	()	(- 1)	()	<u>(Max.)</u>
	(19)	(20)	(21)	(22)	(23)	(24)	(25)	
Dibutyl phthalate (DBP)	ND	ND	ND	ND	ND	ND	ND	0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND	ND	ND	ND	ND	ND	ND	0.1
Benzyl butyl phthalate (BBP)	ND	ND	ND	ND	ND	ND	ND	0.1
Diisononyl phthalate (DINP)	ND	ND	ND	ND	ND	ND	ND	0.1
Diisobutyl phthalate (DIBP)	ND	ND	ND	ND	ND	ND	ND	0.1
Di-n-pentyl phthalate (DPENP)	ND	ND	ND	ND	ND	ND	ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND	ND	ND	ND	ND	ND	ND	0.1
Dicyclohexyl phthalate (DCHP)	ND **********	ND	ND	ND	ND	ND	ND *********	0.1



intertek

<u>Test Report</u>

NUMBER : TSNH00374097-S1

<u>Test item</u>	<u>Result (%)</u>				<u>Limit (%)</u> (Max.)
Dibutyl phthalate (DBP)	(26) ND	(27) ND	(28) ND	(33) 0.04	<u>(Max.)</u> 0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND	ND	ND	ND	0.1
Benzyl butyl phthalate (BBP)	ND	ND	ND	ND	0.1
Diisononyl phthalate (DINP)	ND	ND	ND	ND	0.1
Diisobutyl phthalate (DIBP)	ND	ND	ND	ND	0.1
Di-n-pentyl phthalate (DPENP)	ND	ND	ND	ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND	ND	ND	ND	0.1
Dicyclohexyl phthalate (DCHP)	ND	ND	ND	ND	0.1

The above limit was quoted according to 16 CFR part 1307 approved by U.S. Consumer Product Safety Commission (CPSC) for prohibition of children's toys and child care articles containing specified phthalates.

Remark: ND = Not Detected Detection Limit = 0.01%





<u>Test Report</u>

NUMBER : TSNH00374097-S1

9. Tracking Label Assessment

As per Consumer Product Safety Improvement Act (CPSIA) 2008 Section 103 Tracking Labels For Children Products.

Tracking Label Found on the Packaging:

Name of manufacturer / importer / private labeler:	TAMCO SUMMIT VEHICLE JIANGMEN CO.,LTD.
Location of production:	HANDAN CITY, HEBEI, CHINA
Date code:	April 30,2024
Cohort information:	CU002-2420

Tracking label found on the product:

Name of manufacturer / importer / private labeler:	TAMCO SUMMIT VEHICLE JIANGMEN CO.,LTD.
Location of production:	HANDAN CITY, HEBEI, CHINA
Date code:	April 30,2024
Cohort information:	CU002-2420

Remark:only artwork of label was provided for review.

Note: The tracking label assessment was based on the submitted sample and the information provided by the applicant. There was no verification on the validity of such information.





NUMBER : TSNH00374097-S1

10. Total Lead (Pb) Content for Non-surface Coating

As per section 4.3.5 of the ASTM standard consumer safety specification on toy safety F963-23, test method CPSC-CH-E1002-08.3, was/were used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry.

Test Item		Result in ppm		Reproting Limit	Limit
	(35)	(36)	(37)	<u>(ppm)</u>	<u>(ppm)</u>
Lead(Pb)	ND	ND	ND	10	100

Remark: ppm = parts per million based on dry weight of sample = mg/kg ND= Not detected (Less than reporting limit)

Tested Components: See component list in the last section of this report.

11.Soluble Elements Analysis (ASTM F963-23)

As per section 4.3.5.1(2) and 4.3.5.2(2)(b) of the ASTM standard consumer safety specification on toy safety F963-23, acid extraction method was used and heavy metal elements migration content were determined by Inductively Coupled Argon Plasma Spectrometry.

Test Item		<u>Reporting</u>	Limit		
	(35)	(36)	(37)	Limit (mg/kg)	<u>(mg/kg)</u>
Sol. Barium (Ba)	ND	ND	ND	5	1000
Sol. Lead (Pb)	ND	ND	ND	5	90
Sol. Cadmium (Cd)	ND	ND	ND	5	75
Sol. Antimony (Sb)	ND	ND	ND	5	60
Sol. Selenium (Se)	ND	ND	ND	5	500
Sol. Chromium (Cr)	ND	ND	ND	5	60
Sol. Mercury (Hg)	ND	ND	ND	5	60
Sol. Arsenic (As)	ND	ND	ND	2.5	25

Remark: mg/kg = milligram per kilogram =ppm

Sol. = Soluble spl.wt. = Sample weight ND= Not detected (Less than reporting limit)

Tested components: See component list in the last section of this report.





NUMBER : TSNH00374097-S1

12. Total Lead (Pb) Content In Non-Surface Coating Materials (Substrate)

As per standard operating procedures for determining total Lead (Pb) in children's products, test method(s) CPSC-CH-E1002-08.3 were used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry.

Tested Component	<u>Result (ppm)</u>	<u>Limit (ppm)</u>
(35)	<10	100
(36)	<10	100
(37)	<10	100

The limit was quoted according to U.S. Consumer Product Safety Improvement Act 2008 title I, section 101 for total Lead content in non-surface coating materials (substrate).

Remark: ppm = Parts per million = mg/kg <=less than

Tested Components: See component list in the last section of this report.

13.Phthalate Content

According to CPSC-CH-C1001-09.4, by Gas Chromatographic-Mass Spectrometric (GC-MS) analysis.

<u>Test item</u>	<u>Result (%)</u>			<u>Limit (%) (Max.)</u>
	(35)	(36)	(37)	
Dibutyl phthalate (DBP)	ND	ND	ND	0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND	ND	ND	0.1
Benzyl butyl phthalate (BBP)	ND	ND	ND	0.1
Diisononyl phthalate (DINP)	ND	ND	ND	0.1
Diisobutyl phthalate (DIBP)	ND	ND	ND	0.1
Di-n-pentyl phthalate (DPENP)	ND	ND	ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND	ND	ND	0.1
Dicyclohexyl phthalate (DCHP)	ND	ND	ND	0.1

The above limit was quoted according to 16 CFR part 1307 approved by U.S. Consumer Product Safety Commission (CPSC) for prohibition of children's toys and child care articles containing specified phthalates.

Remark: ND = Not Detected Detection Limit = 0.01%

Tested Component(s): See component list in the last section of this report.

To be continued

Page 18 of 20



ICOLLOK

<u>Test Report</u>

Test components:

NUMBER : TSNH00374097-S1

- (1) Black plastic (body side, rear view mirror, seat, back seat, swith on dashboard & wheel) for sample use
- (2) Black plastic (rear view mirror base, frame body side, exhaust pipe, wheel, pedal, pedal button, back light)
- (3) Black-tranparent plastic (wind mirror)
- (4) Bright red plastic (frame, front mudguard, tank, back seat & head)
- (5) Silver color plastic (handlebar & screw on seat)
- (6) Transparent plastic (front light, side light & wind mirror)
- (7) Red plastic (back light & wheel)(8) White plastic(USB on dashboard)
- (9) White plastic (wheel & wire connection)
- (10)White plastic(wire clasp)
- (11)Red plastic (power button on dashboard)
- (12)Black soft plästic (handle bar)
- (13)Black soft wire(wire skin under the car)
- (14)Yellow soft wire(wire skin under the car)
- (15)Red soft wire(wire skin under the car)
- (16)Silver coating (exhaust pipe, body side, spring, body side near pedal, break disc, button on dashboard & dashboard base)
- (17)Multicolor sticker(speedmeter)
- (18)Black sticker with white printing on dashboard
- (19)Silver color sticker(rearview mirror)
- (20) Multicolor sticker(warning label)
- (21)Multicolor sticker("super motor" on front body side) (22)Multicolor sticker("TAMCO" on exhaust pipe)
- (23)White sticker with black letter(on dashboard)
- (24) Multicolor sticker(charging label)
- (25) Multicolor sticker ("TAMCO 1200"number plate)
 (26) Multicolor sticker ("Tamco 1200" on back between lights)
 (27) Multicolor sticker ("1" on head)
 (28) Multicolor sticker ("TAMCO" on handlebar)

- (29) Silver color metal screw
- (30) Silver color metal gear
- (31)Silver color metal(USB on dashboard)



NLOLLOK

Test Report

NUMBER : TSNH00374097-S1

(32)Black plastic (charger) for sample use
(33)Black plastic with white printing(charger line) for sample use
(34)Silver metal (on charger& charger line) for sample use
(35)Blue plastic for sample (B) use
(36)White plastic for sample (C) use
(37)Pink plastic for sample (D) use

Date sample received: Apr 06, 2021 Testing period: Apr 06, 2021 To Aug 12, 2021

Re : report revision notification

Report number TSNH00374097 dated Aug 12,2021

Please be informed that all the content recorded in the above captioned report will be void. This captioned report is now superseded by a revised report, number TSNH00374097-S1, issued on May 13,2024.

Thank you for your attention.

End of report

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.

