

Test Report

NUMBER : TSNH00374093

Applicant : TAMCO SUMMIT VEHICLE JIANGMEN CO.,LTD.
RM2512,25FLOOR, DEVELOPMENT ROAD, PENGJIANG
ZONE, JIANGMEN CHINA
Attn :COCO TAN

Date : Aug 20,2021

Photo



To be continued

Authorized By :
For Intertek Testing Services
(Tianjin) Ltd.



David Zhang
Senior Manager



Test Report

NUMBER : TSNH00374093

Sample Description:

One (1) submitted sample said to be

Item Name : RIDE ON MOTORCYCLE
Item No. : T2,D2,T7,D7
Style No. : T2,D2,T7,D7
Age grading : 3-8Y
Supplier : TAMCO SUMMIT VEHICLE JIANGMEN CO.,LTD.
Country of Origin : CHINA

Tests Conducted:

As requested by the applicant, for details refer to attached page(s).

Conclusion:

<u>Tested</u> <u>Samples/components</u>	<u>Standard</u>	<u>Result</u>
Submitted Sample	U.S. ASTM F963-17 Standard Consumer Safety Specification for Toy Safety – Physical and mechanical test and Flammability part	Pass
(19&20)	U.S. ASTM F963-17 for total Lead content-surface coating	Pass
(1,2&3),(4,5&6), (7,8&9),(10&36), (11,12&13),(14), (15,16&17),(18),(21), (22),(23),(24),(25),(26),	U.S. ASTM F963-17 for total Lead content-non-surface coating	Pass
(27),(28),(29),(30,31&32), (33,34&35),(37),(38)& (39)	Consumer Product Safety Improvement Act (CPSIA) 2008 Section 103 Tracking Labels for Children Products	Pass

To be continued

Authorized By :
For Intertek Testing Services
(Tianjin) Ltd.



David Zhang
Senior Manager



Intertek Testing Service (Tianjin) Ltd.
天祥(天津)质量技术服务有限公司

No. 7 Guiyuan Road, Huayuan Hi-Tech
Park, Tianjin, 300384 China
天津华苑新技术产业园区桂苑路7号
邮编 300384

Tel +86 22 8371 4973
Fax +86 22 8371 2205
www.intertek.com.cn
www.intertek.com

Test Report

NUMBER : TSNH00374093

(1),(2),(3),(4),(5),(6),(7), (8),(9),(10),(11),(12),(13), (14),(15),(16),(17),(18), (21),(22),(23),(24),(25), (26),(27),(28),(29),(30), (31),(32),(33),(34),(35), (36),(37),(38)&(39)	U.S. ASTM F963-17 section 4.3.5.2(2)(b) for soluble elements content for non-surface coating materials	Pass
(19)&(20)	U.S. ASTM F963-17 for soluble elements content in surface coating	Pass
(19&20)	U.S. Code of Federal Regulations title 16 part 1303 for total Lead content in surface coating	Pass
(19&20)	U.S. Consumer Product Safety Improvement Act 2008 title I, section 101 for total Lead content in surface coating	Pass
(1,2&3),(4,5&6), (7,8&9),(10&36), (11,12&13),(14), (15,16&17),(18),(21), (22),(23),(24),(25),(26), (27),(28),(29),(30,31&32), (33,34&35),(37),(38)& (39)	U.S. Consumer Product Safety Improvement Act 2008 title I, section 101 for total Lead content in non-surface coating materials (substrate)	Pass
(1,2&3),(4,5&6), (7,8&9),(10&36), (11,12&13),(14), (15,16&17),(18),(19&20), (21),(22),(23),(24),(25), (26),(27),(28),(29),(37)& (38)	US Consumer Product Safety Improvement Act 2008 Title I, Sec 108(a) & (b)(3) and US 16 CFR Part 1307 for Prohibition of Children's Toys and Child Care Articles Containing Specified Phthalates	Pass

To be continued

Authorized By :
For Intertek Testing Services
(Tianjin) Ltd.



David Zhang
Senior Manager



Test Report

NUMBER : TSNH00374093

1. Toy Tests

As per ASTM Standard Consumer Safety Specification for Toy Safety F963-17.

Applicant's Specified Age Group for Testing : For ages from 3 to 8 years

The submitted samples were undergone the use and abuse tests in accordance with the Federal Hazardous Substances Act (FHSA), Title 16, Code of Federal Regulations : -

Test	FHSA	Parameter
Tip over Test	Section 1500.53(b)	3 times
Torque Test	Section 1500.53(e)	4 in-lbf
Tension Test	Section 1500.53(f)	15 lbf
Compression Test	Section 1500.53(g)	30 lbf

Section	Testing Items	Assessment
4.1	Material Quality	P
4.2	Flammability	P (See test data #1)
4.3.7	Stuffing Materials	NA
4.4	Electrical/Thermal Energy	NA
4.5	Sound-Producing Toys	P
4.6.1	Toys Intended for Children under 36 Months (Small Objects)	NA
4.6.2	Mouth-Actuated Toys	NA
4.6.3	Toys And Games for 36 Months to 72 Months (Small Part Warning)	P
4.7	Accessible Edges	P
4.8	Projections	P
4.9	Accessible Points	P
4.10	Wires Or Rods	NA
4.11	Nails And Fasteners	P
4.12	Plastic Film	P
4.13	Folding Mechanisms and Hinges	NA
4.14	Cords, Straps, and Elastics	NA
4.15	Stability and Over-Load Requirements	P
4.16	Confined Spaces	NA
4.17	Wheels, Tires and Axles	P
4.18	Holes, Clearance, and Accessibility of Mechanisms	P
4.19	Simulated Protective Devices	NA
4.20	Pacifiers	NA
4.21	Projectile Toys	NA
4.22	Teethers and Teething Toys	NA
4.23	Rattles	NA
4.24	Squeeze Toys	NA



Test Report

NUMBER : TSNH00374093

Section	Testing Items	Assessment
4.25	Battery-Operated Toys	P (See test data #2)
4.26	Toys Intended to be Attached to a Crib or Playpen	NA
4.27	Stuffed and Beanbag-Type Toys	NA
4.28	Stroller and Carriage Toys	NA
4.29	Art Materials	NA
4.30	Toy Gun Marking	NA
4.31	Balloons	NA
4.32	Certain Toys with Nearly Spherical Ends	NA
4.33	Marbles	NA
4.34	Balls	NA
4.35	Pompoms	NA
4.36	Hemispheric-Shaped Objects	NA
4.37	Yo Yo Elastic Tether Toys	NA
4.38	Magnets	NA
4.39	Jaw Entrapment in Handles and Steering Wheels	NA
4.40	Expanding Materials	NA
4.41	Toy Chests	NA
5	Labelling Requirement	P #1
6	Instructional Literature	P #1
7	Producer's Markings	P #1
	- Name of Producer (Toy)	Yes
	- Address (Toy)	Yes

Remark: The submitted samples were undergone the tests in accordance with Section 8.5 through Section 8.18 and 8.21 through 8.26 on normal use, abuse and specific tests for different types of toys whichever is applicable.

P = Pass NA = Not Applicable

#1 = Only artwork of instruction and packaging were provided by applicant.

To be continued



Test Report

NUMBER : TSNH00374093

Test data #1

Flammability Test- Solid & Plush toys

As per section 4.2 of the ASTM Standard Consumer Safety Specification On Toy Safety F963-17.

Result = Did Not Ignite

Test data #2

Battery Powered Ride-On Toys

As per ASTM F963-17 consumer safety specification for toy safety section 4.25, 5.15, 6.5, 6.6 and 7.2.

Applicant's specified age group for testing : For ages from 3 to 8 years

Type of battery: 6V, 4.5 Ah, Lead-acid rechargeable battery x 2pc in vehicle

Charger type: Input 100-120 V A.C., Output 12 V D.C.(Provided)

Model: HK012-120100AXU

Electric operated function: Battery powered motion, sound and LED light.

<u>Section</u>	<u>Testing items</u>	<u>Assessment</u>
4.25.1	Battery marking	P
4.25.2	Maximum allowable direct current potential	P
4.25.3	Protection against charging non-rechargeable battery	P
4.25.4	Accessible batteries	NA
4.25.5	Accessible batteries that can fit completely within small part cylinder	P
4.25.6	Isolation of batteries of different types or capacities	NA
4.25.7	Temperature of battery surface	P
4.25.8	Temperature of battery surface or combustion hazard after normal use and abuse test	P
4.25.9	Packaging and Instruction requirement	P
	- 5.15 Non-replaceable battery statement in battery operated toys	P
	- 5.15.2 Button or coin cell batteries	NA
	- 6.5 Instruction on safe usage of battery	P
4.25.10	Battery-powered ride-on toys	P
4.25.10.1	The maximum temperature measured on the insulation of any conductor shall not exceed the temperature rating of the material.	P
4.25.10.2	Battery powered ride on toys shall not present a risk of fire in stalled motor test.	P
4.25.10.3	A battery powered ride on toy designed with a wiring system that has a	NA



Test Report

NUMBER : TSNH00374093

	user replaceable device (fuse type) for the primary circuit protection or a wiring system with user resettable primary circuit protection (manual reset fuse) shall not actuate (open or trip) when tested in accordance with the nuisance tripping test	
4.25.10.4	<p>Switches used in battery powered ride on toys.</p> <ul style="list-style-type: none"> - Polymeric materials in switches used in battery powered ride on toys that are used to support current carrying parts shall carry a minimum flame rating of UI-94 V-0 or have a glow wire ignition rating of 750°C. - The switch body shall not result in a short circuit condition when subjected to the switch endurance test and overload tests. - The switch shall not fail in a mode that could cause the vehicle to run continuously (switch stuck in the “on” position) when subjected to the endurance test and the overload test. 	P
4.25.10.5	<p>User replaceable circuit protection devices in battery powered ride on toys.</p> <ul style="list-style-type: none"> - User replaceable circuit protection devices provided by the manufacturer in battery-powered ride-on toys shall be listed, recognized or certified by a Nationally Recognized Test Laboratory (NRTL) (that is, a laboratory recognized in accordance with 29 CFR 1910) to an appropriate electrical safety standard. - All circuit protection devices used in battery powered ride on toys intended to be replaced by the user shall be replaceable only with the use of a tool or by a design which does not easily allow tempering such as a design requiring excessive force to open. 	NA
4.25.10.6	<p>Batteries and battery chargers.</p> <ul style="list-style-type: none"> - Battery connectors must be constructed of material with a UL94 V-0 flame rating or have a glow wire ignition rating of 750°C. - The battery charging system shall not present a risk of fire due to a short circuit condition applied to any point in the length of a charger/battery. - During charging, battery-charging voltages shall not exceed the recommended charging voltages. - Battery charges must be certified to the appropriate standard body. Reference document of certified body: E504979 	P
4.25.10.7	Wiring connected to the main/motor battery shall be short circuit protected and shall not present the risk of fire.	P
4.25.10.8	Strain relief shall be provided to prevent mechanical stress on wires entering a connector block during routine maintenance.	P
4.25.10.9	<p>Battery powered ride on toys shall comply with the requirements for safety labelling, for additional instructional literature, and for required producer’s markings.</p> <ul style="list-style-type: none"> - 5.15.1 Safety warnings of battery powered ride on toys - 6.6 Instructions - 7.2 Producer’s marking 	P
4.25.11	Toys that contain secondary cells or secondary batteries	NA

Remark: P = Pass NA = Not Applicable

To be continued
Page 7 of 14



Test Report

NUMBER : TSNH00374093

2.Total Lead (Pb) Content

As per section 4.3.5 of the ASTM standard consumer safety specification on toy safety F963-17, test method CPSC-CH-E1001-08.3, CPSC-CH-E1002-08.3 or/and CPSC-CH-E1003-09.1 was/were used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry and AAS.

(I) Surface coating

<u>Tested component</u> (19&20)	<u>Result in ppm</u> <20	<u>Limit (ppm)</u> 90
------------------------------------	-----------------------------	--------------------------

(II) Non-surface coating

<u>Tested component</u>	<u>Result in ppm</u>	<u>Limit (ppm)</u>
(1,2&3)	<10	100
(4,5&6)	<10	100
(7,8&9)	<10	100
(10&36)	<10	100
(11,12&13)	<10	100
(14)	<10	100
(15,16&17)	<10	100
(18)	<10	100
(21)	<10	100
(22)	<10	100
(23)	<10	100
(24)	<10	100
(25)	<10	100
(26)	<10	100
(27)	<10	100
(28)	<10	100
(29)	<10	100
(30,31&32)	<10	100
(33,34&35)	<10	100
(37)	<10	100
(38)	<10	100
(39)	36	100

Remark: ppm = parts per million based on dry weight of sample = mg/kg
 <=less than

Tested Components : See component list in the last section of this report.

To be continued



Test Report

NUMBER : TSNH00374093

3.Soluble Elements Analysis In Non-Surface Coating Materials (Substrate Except Modelling Clay)

As per section 4.3.5.2(2)(b) of the ASTM standard consumer safety specification on toy safety F963-17, acid extraction method was used and heavy metal elements migration content were determined by Inductively Coupled Argon Plasma Spectrometry.

	<u>Result (ppm)</u>										<u>Limit (ppm)</u>
	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	
Sol. Barium (Ba)	<5	<5	<5	<5	<5	<5	17	<5	<5	<5	1000
Sol. Lead (Pb)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	90
Sol. Cadmium (Cd)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	75
Sol. Antimony (Sb)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Selenium (Se)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	500
Sol. Chromium (Cr)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Mercury (Hg)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Arsenic (As)	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	25

	<u>Result (ppm)</u>								<u>Limit (ppm)</u>
	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	
Sol. Barium (Ba)	<5	<5	<5	<5	<5	<5	<5	<5	1000
Sol. Lead (Pb)	<5	<5	<5	<5	<5	<5	<5	<5	90
Sol. Cadmium (Cd)	<5	<5	<5	<5	<5	<5	<5	<5	75
Sol. Antimony (Sb)	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Selenium (Se)	<5	<5	<5	<5	<5	<5	<5	<5	500
Sol. Chromium (Cr)	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Mercury (Hg)	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Arsenic (As)	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	25

	<u>Result (ppm)</u>										<u>Limit (ppm)</u>
	(21)	(22)	(23)	(24)	(25)	(26)	(27)	(28)	(29)	(30)	
Sol. Barium (Ba)	<5	<5	<5	17	<5	<5	<5	<5	<5	<5	1000
Sol. Lead (Pb)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	90
Sol. Cadmium (Cd)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	75
Sol. Antimony (Sb)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Selenium (Se)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	500
Sol. Chromium (Cr)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Mercury (Hg)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Arsenic (As)	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	25

To be continued



Test Report

NUMBER : TSNH00374093

	<u>Result (ppm)</u>										<u>Limit (ppm)</u>
	(31)	(32)	(33)	(34)	(35)	(36)	(37)	(38)	(39)		
Sol. Barium (Ba)	<5	<5	<5	<5	19	<5	<5	<5	<5	<5	1000
Sol. Lead (Pb)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	90
Sol. Cadmium (Cd)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	75
Sol. Antimony (Sb)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Selenium (Se)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	500
Sol. Chromium (Cr)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Mercury (Hg)	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	60
Sol. Arsenic (As)	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	25

Remark: Sol. = soluble
ppm = parts per million = mg/kg
spl.wt. = sample weight

Tested components : See component list in the last section of this report.

4.Soluble Elements Analysis In Surface Coating

As per section 4.3.5.1(2) of the ASTM standard consumer safety specification on toy safety F963-17, acid extraction method was used and heavy metal elements migration content were determined by Inductively Coupled Argon Plasma Spectrometry.

	<u>Result (ppm)</u>		<u>Limit (ppm)</u>
	(19)	(20)	
Sol. Barium (Ba)	22	320	1000
Sol. Lead (Pb)	<5	<5	90
Sol. Cadmium (Cd)	<5	<5	75
Sol. Antimony (Sb)	<5	<5	60
Sol. Selenium (Se)	<5	<5	500
Sol. Chromium (Cr)	<5	14	60
Sol. Mercury (Hg)	<5	<5	60
Sol. Arsenic (As)	<2.5	<2.5	25

Remark: Sol. = soluble
ppm = parts per million based on dry weight of sample = mg/kg
spl.wt. = sample weight

Tested components : See component list in the last section of this report.

To be continued



Test Report

NUMBER : TSNH00374093

5.Total Lead (Pb) Content In Surface Coating

As per standard operating procedure for determining Lead (Pb) in paint and other similar surface coatings (April 26, 2009), test method CPSC-CH-E1003-09 was used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry.

<u>Tested Component</u> (19&20)	<u>Result (ppm)</u> <20	<u>Limit (ppm)</u> 90
------------------------------------	----------------------------	--------------------------

Remark: ppm = Parts per million based on dry weight of sample = mg/kg
< = Less Than

Tested Components : See component list in the last section of this report.

6.Total Lead (Pb) Content In Non-Surface Coating Materials (Substrate)

As per standard operating procedures for determining total Lead (Pb) in children's products, test method(s) CPSC-CH-E1002-08.1 and CPSC-CH-E1001-08.1 were used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry.

<u>Tested Component</u>	<u>Result (ppm)</u>	<u>Limit (ppm)</u>
(1,2&3)	<10	100
(4,5&6)	<10	100
(7,8&9)	<10	100
(10&36)	<10	100
(11,12&13)	<10	100
(14)	<10	100
(15,16&17)	<10	100
(18)	<10	100
(21)	<10	100
(22)	<10	100
(23)	<10	100
(24)	<10	100
(25)	<10	100
(26)	<10	100
(27)	<10	100
(28)	<10	100
(29)	<10	100
(30,31&32)	<10	100
(33,34&35)	<10	100
(37)	<10	100
(38)	<10	100
(39)	36	100

Remark: ppm = Parts per million = mg/kg
< = Less Than

Tested Components : See component list in the last section of this report.

To be continued

Page 11 of 14



Test Report

NUMBER : TSNH00374093

7. Phthalate Content

With reference to CPSC-CH-C1001-09.4, by Gas Chromatographic-Mass Spectrometric (GC-MS) analysis.

Test item	Result (%)					Limit (%) (Max.)
	(1,2&3)	(4,5&6)	(7,8&9)	(10&36)	(11,12&13)	
Dibutyl phthalate (DBP)	ND	ND	ND	ND	ND	0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND	ND	ND	ND	ND	0.1
Benzyl butyl phthalate (BBP)	ND	ND	ND	ND	ND	0.1
Diisononyl phthalate (DINP)	ND	ND	ND	ND	ND	0.1
Diisobutyl phthalate (DIBP)	ND	ND	ND	ND	ND	0.1
Di-n-pentyl phthalate (DPENP)	ND	ND	ND	ND	ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND	ND	ND	ND	ND	0.1
Dicyclohexyl phthalate (DCHP)	ND	ND	ND	ND	ND	0.1

Test item	Result (%)					Limit (%) (Max.)
	(14)	(15,16&17)	(18)	(19&20)	(21)	
Dibutyl phthalate (DBP)	ND	ND	ND	ND	ND	0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND	ND	0.03	ND	ND	0.1
Benzyl butyl phthalate (BBP)	ND	ND	ND	ND	ND	0.1
Diisononyl phthalate (DINP)	ND	ND	ND	ND	ND	0.1
Diisobutyl phthalate (DIBP)	ND	ND	ND	ND	ND	0.1
Di-n-pentyl phthalate (DPENP)	ND	ND	ND	ND	ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND	ND	ND	ND	ND	0.1
Dicyclohexyl phthalate (DCHP)	ND	ND	ND	ND	ND	0.1

Test item	Result (%)					Limit (%) (Max.)
	(22)	(23)	(24)	(25)	(26)	
Dibutyl phthalate (DBP)	ND	ND	ND	ND	ND	0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND	ND	ND	ND	ND	0.1
Benzyl butyl phthalate (BBP)	ND	ND	ND	ND	ND	0.1
Diisononyl phthalate (DINP)	ND	ND	ND	ND	ND	0.1
Diisobutyl phthalate (DIBP)	ND	ND	ND	ND	ND	0.1
Di-n-pentyl phthalate (DPENP)	ND	ND	ND	ND	ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND	ND	ND	ND	ND	0.1
Dicyclohexyl phthalate (DCHP)	ND	ND	ND	ND	ND	0.1

To be continued



Test Report

NUMBER : TSNH00374093

<u>Test item</u>	<u>Result (%)</u>					<u>Limit (%)</u>
	(27)	(28)	(29)	(37)	(38)	(Max.)
Dibutyl phthalate (DBP)	ND	ND	ND	ND	ND	0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND	ND	ND	ND	ND	0.1
Benzyl butyl phthalate (BBP)	ND	ND	ND	ND	ND	0.1
Diisononyl phthalate (DINP)	ND	ND	ND	ND	ND	0.1
Diisobutyl phthalate (DIBP)	ND	ND	ND	ND	ND	0.1
Di-n-pentyl phthalate (DPENP)	ND	ND	ND	ND	ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND	ND	ND	ND	ND	0.1
Dicyclohexyl phthalate (DCHP)	ND	ND	ND	ND	ND	0.1

The above limit was quoted according to 16 CFR part 1307 approved by U.S. Consumer Product Safety Commission (CPSC) for prohibition of children's toys and child care articles containing specified phthalates.

Remark: ND = Not Detected
Detection Limit = 0.01%

Tested Component(s): See component list in the last section of this report.

To be continued



Test Report

NUMBER : TSNH00374093

Test components:

- (1) Black plastic (front mudguard, exhaust pipe, frame, back mudguard, back light, front light, rear view mirror & dashboard) for sample use
- (2) Black plastic (head, seat, switch on dashboard & pedal)
- (3) Black plastic (tyre & rims)
- (4) Bright red plastic (frame&head)
- (5) Silver color plastic (tailstock, screw on tailstock, frame & brake disc)
- (6) Red plastic (button on dashboard)
- (7) Red plastic switch (dashboard)
- (8) Transparent plastic (lights)
- (9) Red plastic (back light)
- (10) White plastic (USB on dash board)
- (11) Black soft plastic (handle bar)
- (12) Black soft plastic (tyre)
- (13) Black soft plastic (fastener on handlebar)
- (14) Black soft plastic (wire cover)
- (15) Red soft plastic (wire skin)
- (16) Green soft wire (wire skin)
- (17) Black soft wire (wire skin)
- (18) Black sticker with white printing on dashboard
- (19) Silver coating (exhaust pipe)
- (20) Black coating (handlebar & training wheel)
- (21) Black rubber (training wheel)
- (22) Multicolor sticker (dashboard)
- (23) Multicolor sticker (rearview mirror)
- (24) Multicolor sticker (warning label)
- (25) Multicolor sticker (seat side)
- (26) Multicolor sticker (exhaust pipe)
- (27) Multicolor sticker (charging label) 补 10 张
- (28) Multicolor sticker (back)
- (29) Multicolor sticker (frame)
- (30) Silver color metal screw (seat) 补 2 个
- (31) Silver color metal nut & screw (handlebar)
- (32) Silver color metal nut & screw (frame)
- (33) Silver color metal nut (training wheel)
- (34) Silver color metal (front wheel)
- (35) Silver color metal (USB on dashboard) 补 1 个
- (36) Black plastic (charger) for sample use
- (37) Black plastic with white printing (charger line) for sample use
- (38) Yellow sticker with black printing (charger) for sample use 补 5 个
- (39) Silver metal (on charger & charger line) for sample use

Date sample received: Apr 25, 2021

Testing period: Apr 25, 2021 To Aug 19, 2021

End of report

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.

