

**Test Report**

Number: SHAH01609736

Applicant: SHANGHAI HAPPY CHILDREN FACTORY  
NO.1002, XINJIANFENG,  
JINGYANG VILLAGE, LANG XIA TOWN,  
JIN SHAN DISTRICT, SHANGHAI  
Attn: -

Date: 17 Oct, 2023

Sample Description:

One(1) group of submitted sample said to be :  
Item Name : Battery Operated car,Ride-On Car  
Item No. : A017  
Labelled Age Group : 18months+  
Packaging Provided By Applicant : Yes  
Goods Exported To : USA  
Country Of Origin : China

Tests Conducted:

As requested by the applicant, for details refer to attached page(s).

Conclusion:

Tested Samples	Standard	Result
Submitted Sample	ASTM F963-17 Section 4.25, 5.15, 6.5, 6.6 & 7.2 for Battery-Powered Ride-On Toys	Pass

Prepared And Checked By:  
For Intertek Testing Services Wuxi Ltd.



Bill Zhang  
General Manager



## Test Report

Number: SHAH01609736

### Tests Conducted

#### 1. Battery Powered Ride-On Toys

As per ASTM F963-17 consumer safety specification for toy safety section 4.25, 5.15, 6.5, 6.6 and 7.2.

Applicant's specified age group for testing: Over 18 months.

Type of battery: Vehicle : 6 V, 4.5 Ah, Lead-acid rechargeable battery X 1pc.

Charger: Type: Input 110-120V A.C., Output 8 V D.C.(Provided)

Model: ZNL-U080050

Electric operated function: Battery powered Sound, LED, Motion.

Section	Testing items	Assessment
4.25.1	Battery marking	NA
4.25.2	Maximum allowable direct current potential	P
4.25.3	Protection against charging non-rechargeable battery	P
4.25.4	Accessible batteries	P
4.25.5	Accessible batteries that can fit completely within small part cylinder	NA
4.25.6	Isolation of batteries of different types or capacities	NA
4.25.7	Temperature of battery surface	P
4.25.8	Temperature of battery surface or combustion hazard after normal use and abuse test	P
4.25.9	Packaging and Instruction requirement	
	- 5.15 Non-replaceable battery statement in battery operated toys	NA
	- 5.15.2 Button or coin cell batteries	NA
	- 6.5 Instruction on safe usage of battery	NA
4.25.10	Battery-powered ride-on toys	P
4.25.10.1	The maximum temperature measured on the insulation of any conductor shall not exceed the temperature rating of the material.	P
4.25.10.2	Battery powered ride on toys shall not present a risk of fire in stalled motor test.	P
4.25.10.3	A battery powered ride on toy designed with a wiring system that has a user replaceable device (fuse type) for the primary circuit protection or a wiring system with user resettable primary circuit protection (manual reset fuse) shall not actuate (open or trip) when tested in accordance with the nuisance tripping test	NA
4.25.10.4	Switches used in battery powered ride on toys.	P
	- Polymeric materials in switches used in battery powered ride on toys that are used to support current carrying parts shall carry a minimum flame rating of UI-94 V-0 or have a glow wire ignition rating of 750°C.	
	- The switch body shall not result in a short circuit condition when subjected to the switch endurance test and overload tests.	
	- The switch shall not fail in a mode that could cause the vehicle to run continuously (switch stuck in the "on" position) when subjected to the endurance test and the overload test.	
4.25.10.5	User replaceable circuit protection devices in battery powered ride on toys.	NA
	- User replaceable circuit protection devices provided by the manufacturer in battery-powered ride-on toys shall be listed, recognized or certified by a Nationally Recognized Test Laboratory (NRTL) (that is, a laboratory recognized in accordance with 29 CFR 1910) to an appropriate electrical safety standard.	
	- All circuit protection devices used in battery powered ride on toys intended to be replaced by the user shall be replaceable only with the use of a tool or by a design which does not easily allow tempering such as a design requiring excessive force to open.	
4.25.10.6	Batteries and battery chargers.	P
	- Battery connectors must be constructed of material with a UL94 V-0 flame rating or have a glow wire ignition rating of 750°C.	



**Test Report**

Number: SHAH01609736

Tests Conducted

- The battery charging system shall not present a risk of fire due to a short circuit condition applied to any point in the length of a charger/battery.
- During charging, battery-charging voltages shall not exceed the recommended charging voltages.
- Battery charges must be certified to the appropriate standard body.

Reference document of certified body : E525112

4.25.10.7	Wiring connected to the main/motor battery shall be short circuit protected and shall not present the risk of fire.	P
4.25.10.8	Strain relief shall be provided to prevent mechanical stress on wires entering a connector block during routine maintenance.	P
4.25.10.9	Battery powered ride on toys shall comply with the requirements for safety labelling, for additional instructional literature, and for required producer's markings. - 5.15.1 Safety warnings of battery powered ride on toys - 6.6 Instructions - 7.2 Producer's marking	P
4.25.11	Toys that contain secondary cells or secondary batteries	NA

Remark : P = Pass                      NA = Not Applicable

Date Sample Received: 16 Oct , 2023  
Testing Period: 07 Oct , 2023 To 16 Oct , 2023

\*\*\*\*\*



**Test Report**

Number: SHAH01609736

Tests Conducted

Photo



70x40mm



A017 70x50mm

**WARNING:**

To reduce the risk of injury, adult supervision is required.  
Never use in roadways, near motor vehicles, on or near steep inclines or steps, swimming pools or other bodies of water; always wear shoes, and never allow more than 1 rider.

ALL NEW MATERIAL、IRON PARTS  
CONSISTING OF:PP NEW MATERIAL/IRON PARTS  
Batch NO.RXY230703011A-R  
MADE FROM  
SHANGHAI HAPPY CHILDREN FACTORY  
No.1002 Langping road, Langxia town, Jinshan district,  
Shanghai, China  
FINISHED SIZES: 82.5\*44\*56CM  
MADE IN CHINA, SHANGHAI  
MANUFACTURED IN: 2023.08  
HC SHA2308  
Item No.: A017

\*\*\*\*\*  
End Of Report

The statements of conformity reported have considered the decision rule agreed, namely that Intertek have taken account of measurement uncertainty as calculated by Intertek, and applied according to ILAC-G8/09:2019 (Non-binary acceptance based on guard band  $w = U$ ) except designation from the customer, regulation or test specification. This decision rule only applies to the numeric test results.

The sample(s) and sample information hereto are provided by the client who shall be solely responsible for the authenticity and integrity thereof. The results shown in this report relate only to the sample(s) received and tested. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct. This report shall not be reproduced unless with prior written approval from Intertek Testing Services Wuxi Ltd.