Deepen Quadruple Planter Box Installation



63"L*15.75"W*14.17"D

Parts List:

Base Plate	Water Barrier	Water Pipe		Upright Column	Blocking Plug	Cover Strip	Cover Cap	connecting rod	Connected feet
4	4	3	20	32	10	16	16	6	6
								/	A

Step 1. Install the Base Plate

The four sides of the base plate with slot and buckle, each two base plates aligned with the slots and buckle, put the slot side above the buckled side, then press to complate the docking.

Step 2. Install Side Panels

Each Side panel have 4 foot clasps, put them into the slots which in the base plate, them push the side panel a little to the left side to tighted the connection.

Step 3. Install the Upright Column

The shirinked side of the Colume down side, align the column's slot side to the side panles' buckle, then push the column till it insert the hole down side.

Step 4. Install the Upper Side Panels

Align the upper side panle's four foot clasps with the below one's slots, put them in and push the upper one to left side to tighted the connection.

Step 5. Install the Upper Column

















The shirinked side of the Colume down side, align the column's slot side to the side panles' buckle, then push the column till it insert the hole down side.

Step 6. Water Pipe Communicator

Each Water pipe comes with 2 rubber sealing ring, handle the fat side and insert the thin side to the drain holes which two base plate connecte.

Whatever left or right.

Step 7. Water Barrier and Cover Strips

Put the water barrier on the base plase, align the cover strip's 4 foot clasps with the holes in the top of side pannels, then press the strips.













Step 8.Install the connecting rod connecting foot

Insert the connecting rods into the slots in sequence

Place the connecting feet on the chassis support feet





Step 9. Cover Cap

Install the cover cap into the top of the column.

Step 10. Water Blacking Plug

Incert the water blacking plug into the drain holes arounding and finish the installation.





